



ACEX Ex e certified junction boxes and enclosures



Certification: Certification No's: SIRA 08 ATEX 3212, IEC Ex SIR 13.0038X and SIRA 11 3132U

Approved to: Ex II 2GD Ex e IIC T5 and T6, Ex II 1 G/2 D Ex ia IIC T6, Ex II2 (1) G/2D Ex ia IIC T6,

Ingress protection level options: IP66, 67 and 68

Ambient temperature: -40 to +65°C with appropriate gasket

CE-TEK ATEX features

- ✓ 316L stainless steel and various finish options including orbital, bead-blast, electro-polished and painted.
- ✓ 1.5mm or 2mm wall thickness as standard.
- ✓ Available with plain sides and up to 4 gland plates. Gland plate thickness options 2.0mm to 6.0mm.
- ✓ Available as empty enclosures or with a wide range of terminals.
- ✓ Fitted with internal/external M6 or M10 earth stud.
- ✓ 3mm thick external wall mounting brackets, with a slotted top bracket for ease of mounting.
- ✓ Hank bushes fitted as standard
- ✓ Detachable hinged lid on ACEX231513 and above.
- ✓ Padlock hasp door locking facility on ACEX231513 and above
- ✓ Also available in non-standard sizes and 304L stainless steel.

Product Code	Height mm	Width mm	Depth mm	Max no. of terminals (2.5mm ²)	Max no. of entries (ISO M20)			
					Bottom	Left	Right	Top
ACEX111165	110	110	65**	5	2	2	2	2
ACEX121280	120	120	80**	8	3	3	3	3
ACEX151290	150	120	80**	8	3	3	3	3
ACEX151590	150	150	90**	8	4	4	4	4
ACEX191590	190	150	90**	15	4	5	5	4
ACEX191910	190	190	100**	15	6	6	6	6
ACEX231513	229	152	130	29	4	6	6	4
ACEX262615	260	260	150	68	12	12	12	12
ACEX262620	260	260	200	68	18	18	18	18
ACEX303015	306	306	150	86	14	14	14	14
ACEX303020	306	306	200	86	21	21	21	21
ACEX382615	380	260	150	104	12	18	18	12
ACEX382620	380	260	200	104	18	27	27	18
ACEX383815	380	380	150	118	18	14	14	18
ACEX383820	380	380	200	118	36	27	27	36
ACEX463815	458	382	150	134	18	22	22	18
ACEX463820	458	382	200	134	27	33	33	27
ACEX484815	480	480	150	140	24	24	24	24
ACEX484820	480	480	200	140	36	36	36	36
ACEX503515	500	350	150	110	16	24	24	16
ACEX503520	500	350	200	110	24	36	36	24
ACEX624515	620	450	150	182	22	30	30	22
ACEX624520	620	450	200	182	33	45	45	33
ACEX765115	762	508	150	250	24	38	38	24
ACEX765120	762	508	200	250	36	57	57	36
ACEX916120	914	610	200	784	45	66	66	45
ACEX916130	914	610	300	784	90	132	132	90
ACEX1207821	1177	777	210	1035	57	87	87	57
ACEX1207830	1177	777	300	1035	114	174	174	114