



CE-TEK Limited, Units 1~4, Tideswell Business Park, Tideswell, Derbyshire, SK18 8NY

Tel: 01298 872233. Fax: 01298 871155. www.ce-tek.co.uk sales@ce-tek.co.uk



Certificate information: Certification numbers: SIRA 08 ATEX 3213 and IECEx SIR 13.0039X

Approved to: Ex II 1 GD, Ex ia IIC T5 and T6, Ex ta IIIC T85°C and T100°C, Ex II 1 2 GD, Ex e IIC T5 and T6, Ex tb IIIC T85°C and T100°C

Ingress protection levels: IP66, 67 and 68

Ambient temperature: -55 to 120°C with appropriate gasket

CE-TEK CEP features

- ✓ Constructed from Glass Reinforced Polyester (GRP)
- ✓ ATEX versions finished in black (RAL 9005) carbon loaded anti-static GRP.
- ✓ Standard versions are finished in grey (RAL 7001). Also available in other colours+
- ✓ Available as empty enclosures or fitted with terminals.
- ✓ ATEX versions are fitted with internal/external M6 earth stud.
- ✓ Lids fitted with stainless steel fasteners
- ✓ Available with RFI shielding for EMC compliance
- ✓ Available with internal/external hinges, mounting plates, external mounting feet and wire lock screws.

* Available as an IP68 enclosure up to 30m depth

Product Code	Height mm	Width mm	Depth mm	Max no. of terminals (2.5 mm ²)	Max no. of entries (ISO M20)
CEP807555	80	75	55	7	2
CEP807575	80	75	75	7	4
CEP117555	110	75	55	11	3
CEP117575	110	75	75	11	6
CEP167555	160	75	55	17	5
CEP167575	160	75	75	17	8
CEP197555	190	75	55	18	7
CEP197575	190	75	75	18	12
CEP237555	230	75	55	35	8
CEP237575	230	75	75	35	12
CEP121290*	122	120	90	14	6
CEP221290*	220	120	90	34	14
CEP161690	160	160	90	20	9
CEP261690*	260	160	90	40	17
CEP361690	360	160	90	60	26
CEP561690	560	160	90	100	40
CEP252512	255	250	120	78	24
CEP252516	255	250	160	78	24
CEP402512	400	250	120	136	42
CEP402516	400	250	160	136	42
CEP404016	400	405	120	168	42
CEP404020	400	405	200	204	36
CEP602512	600	250	120	214	60